





# CoverLite® MR9" and MR12"

## Technical and Loading Guidelines

Product	Overall Width	Overall Length	Net Coverage	Pitch	Depth	Thickness	Available Colors
MR9"	38"	Up to 39'	36"	9"	.75"	.031"	Clear, Opal and Bronze
							
MR9" FLAT	38"	Up to 39'	36"	9"	.625"	.031"	Clear and Opal
							
MR12"	38"	Up to 39'	36"	12"	1.25"	.031"	Clear and Opal
							
RIDGECAP	24"	10' 6"	—	—	—	.047"	Clear and Opal
							

**Light Transmission:** Clear 90%, Opal 66%, Bronze 31%

**Loading Guide:** Maximum 25 psf. wind load with 3' on center vertical supports

**Purlin Spacing:** Maximum horizontal spacing 36" at ridge and gutter and 48" maximum purlin spacing in the mid-span

**Pre-Drill Screw Holes:** 5/64" larger than screw size to allow for expansion and contraction of panel

**Screws & Washers:** Use 1" or 2" #10 Woodmate w/wing or 1" or 2" #12 Self-Drilling/Self Tapping screw with a minimum 1/2" neoprene bonded washer

**Material Weight:** .24 lbs/sq.ft.

**Roof Pitch:** Minimum 3:12

