

Dealer:	Date:	<input type="checkbox"/> Quote Only <input type="checkbox"/> Dealer PO
Attn:	Phone:	Fax:
<b>SERIES 1100 SMOKE VENTS ORDER FORM</b>		

UL 793 CERTIFIED				
	SINGLE LID CURB MOUNT	SINGLE LID SELF FLASHING CURB	DOUBLE LID CURB MOUNT	DOUBLE LID SELF FLASHING CURB
QTY				
HEIGHT	NA	<input type="checkbox"/> 9" tall <input type="checkbox"/> 12" tall <input type="checkbox"/> _____	NA	<input type="checkbox"/> 9" tall <input type="checkbox"/> 12" tall <input type="checkbox"/> _____
STANDARD SIZE ROUGH OPENING	<input type="checkbox"/> 48" x 48" <input type="checkbox"/> 48" x 96" <input type="checkbox"/> 37" x 75" <input type="checkbox"/> 46.25" x 69.5" <input type="checkbox"/> 46.25" x 89.5"	<input type="checkbox"/> 48" x 48" <input type="checkbox"/> 48" x 96" <input type="checkbox"/> 37" x 75" <input type="checkbox"/> 46.25" x 69.5" <input type="checkbox"/> 46.25" x 89.5"	<input type="checkbox"/> 48" x 48" <input type="checkbox"/> 48" x 96"	<input type="checkbox"/> 48" x 48" <input type="checkbox"/> 48" x 96"
NOMINAL 4' x 8' MAX SIZE				
CUSTOM SIZE	OUTSIDE CURB DIM <input type="checkbox"/>	ROUGH OPENING <input type="checkbox"/>	OUTSIDE CURB DIM <input type="checkbox"/> 51.5" x _____"	ROUGH OPENING <input type="checkbox"/> 48" x _____"
GLAZING	<b>Non-Insulated</b> Acrylic <input type="checkbox"/> clear <input type="checkbox"/> white <b>Insulated</b> Co-Polyester / Acrylic <input type="checkbox"/> clear / clear <input type="checkbox"/> white / clear	<b>Non-Insulated</b> Acrylic <input type="checkbox"/> clear <input type="checkbox"/> white <b>Insulated</b> Co-Polyester / Acrylic <input type="checkbox"/> clear / clear <input type="checkbox"/> white / clear	<b>Insulated</b> Co-Polyester / Acrylic <input type="checkbox"/> clear / clear <input type="checkbox"/> white / clear	<b>Insulated</b> Co-Polyester / Acrylic <input type="checkbox"/> clear / clear <input type="checkbox"/> white / clear
FUSIBLE LINK	<input type="checkbox"/> 165° UL Listed Link <input type="checkbox"/> 212° UL Listed Link <input type="checkbox"/> 286° UL Listed Link <input type="checkbox"/> 350° UL Listed Link	<input type="checkbox"/> 165° UL Listed Link <input type="checkbox"/> 212° UL Listed Link <input type="checkbox"/> 286° UL Listed Link <input type="checkbox"/> 350° UL Listed Link	<input type="checkbox"/> 165° UL Listed Link <input type="checkbox"/> 212° UL Listed Link <input type="checkbox"/> 286° UL Listed Link <input type="checkbox"/> 350° UL Listed Link	<input type="checkbox"/> 165° UL Listed Link <input type="checkbox"/> 212° UL Listed Link <input type="checkbox"/> 286° UL Listed Link <input type="checkbox"/> 350° UL Listed Link
MANUAL RELEASE	exterior included <input type="checkbox"/> add interior	exterior included <input type="checkbox"/> add interior	exterior included <input type="checkbox"/> add interior	exterior included <input type="checkbox"/> add interior
OPTIONAL ACCESSORIES				
FALL PROTECTION SAFETY GRID	<input type="checkbox"/> ELITE (cable) <input type="checkbox"/> DEFENSE (bar)	<input type="checkbox"/> ELITE (cable) <input type="checkbox"/> DEFENSE (bar)	<input type="checkbox"/> ELITE (cable) <input type="checkbox"/> DEFENSE (bar)	<input type="checkbox"/> ELITE (cable) <input type="checkbox"/> DEFENSE (bar)



**Series 1100 Smoke and Heat Vent**

CrystaLite's Smoke Vents are made with aircraft grade 6063-T5 aluminum, with welded corners on internal and external framing members, which provides maximum durability and a weather tight enclosure.

**Mounting**

Smoke Vents are a curb mounted product, with the option of being provided with self-flashing insulated curbs. CrystaLite's Smoke and Heat Vents, and self-flashing insulated curbs, are available in both standard and custom sizes.

**Glazing**

Domes are made with high impact resistant co-polyester sheeting and impact modified acrylic. Domes are available in two color options, clear for maximum light and translucent white for optimal light diffusion.

**Releases**

UL Listed fusible links release the smoke vent lid automatically when the internal heat of the building reaches that of the fusible link's specified temperature. External manual releases are included, internal manual release is optional.

Estimated Dealer Cost   
quote good for 30 days



**EVERETT**  
phone: 1-800-666-6065  
fax: 425-258-6734

**SPOKANE**  
phone: 1-800-382-5403  
fax: 509-921-2137

**SALEM**  
phone: 1-800-664-1257  
fax: 503-391-0974